

▼ Shown from left to right: JHA-356, JHA-156, JTA-76



## JHA, JTA Series

Capacity:  
**7-150 tons**

Stroke:  
**3.00-6.13 inch**

Maximum Operating Pressure:  
**10,000 psi**



**Toe-Lift and Load Skates**  
See the tool section in this catalog for more toe-lifts and load skates for easy load transportation.

Page: 176

- All-directional operation on 7, 15 and 35 ton models
- Two-directional operation (vertical and horizontal) on 75 and 150 ton models
- Internal relief valve to prevent overloading
- Machined flat front and bottom surfaces permit flush alignment in tight corners
- All models include pumping handle
- Chrome plated plungers

▼ Enerpac high quality aluminum jacks are a great tool for precise positioning out in the field.



Style	Jack Capacity (tons)	Toe Height (in)	Stroke (in)	Model Number	Jack Effective Area (in <sup>2</sup> )	Collapsed Height (in)	Extended Height (in)	Bottom Plate Dimensions (W x L) (in)	Plunger Diameter (in)	Pump Speed	Weight (lbs)
Conventional Jack	7	–	3.00	JHA-73	1.49	5.25	8.25	2.88 x 6.25	1.19	Single	11
	15	–	6.06	JHA-156	3.14	9.75	15.81	3.63 x 9.38	1.63	Single	29
	35	–	6.13	JHA-356	7.07	10.13	16.25	4.63 x 10.00	2.13	Single	40
	75	–	6.06	JHA-756	15.90	11.25	17.31	6.88 x 12.81	4.50	Single	94
	150	–	6.13	JHA-1506	30.68	12.88	19.00	9.50 x 16.06	6.25	2-Speed	210
Toe-Lift Jack	7	2.00	6.06	JTA-76	3.14	12.56	18.63	3.63 x 11.63	1.63	Single	58
	17	2.00	6.13	JTA-176	7.07	14.19	20.31	4.63 x 13.13	2.13	Single	86
	35	2.56	6.06	JTA-356	15.90	16.63	22.69	6.88 x 16.63	3.25	Single	210