

Premium Steel Jacks

▼ Shown clockwise from left: JH-1006, JH-506, JH-306



JH Series

Capacity:
30-100 tons

Stroke:
6.06-6.13 inch

Maximum Operating Pressure:
10,000 psi



Toe-Lift and Load Skates
See the tool section in this catalog for more toe-lifts and load skates for easy load transportation.

Page: **176**

- Chrome plated plungers
- Machined flat front and bottom surfaces permit flush alignment in tight corners
- Internal relief valve to prevent overloading
- All models include pumping handle
- Two-directional operation (vertical and horizontal)

▼ Creativity is the limit with Enerpac Steel Jacks.



| Jack Capacity (tons) | Stroke (in) | Model Number | Jack Effective Area (in ²) | Collapsed Height (in) | Extended Height (in) | Bottom Plate Dimensions W x L (in) | Plunger Diameter (in) | Pump Speed | Weight (lbs) |
|-------------------------|----------------|--------------|---|--------------------------|-------------------------|--|--------------------------|------------|-----------------|
| 30 | 6.13 | JH-306 | 5.94 | 10.00 | 16.13 | 3.75 x 9.56 | 2.75 | Single | 59 |
| 50 | 6.09 | JH-506 | 9.62 | 10.25 | 16.34 | 5.00 x 10.19 | 3.50 | 2-Speed | 90 |
| 100 | 6.06 | JH-1006 | 20.63 | 11.31 | 17.37 | 7.13 x 12.94 | 5.12 | 2-Speed | 184 |